

The listing of the claims will replace the previous version,
and the listing of claims:

LISTING OF CLAIMS

1. (currently amended) A brake apparatus comprising:

921
b1
a master cylinder having an input shaft which travels according to travel of an operational member for a service braking maneuver, a master cylinder pressure chamber, and a master cylinder piston which develops a master cylinder pressure in said master cylinder pressure chamber according to the travel of said input shaft,

a pump which is driven ~~in~~ by the service braking maneuver,

a braking force control device which receives operational conditions of the service braking and another braking different from the service braking, said braking force control device controlling controls, in the service braking maneuver, the a discharge pressure of said pump according to ~~at least either the operational condition for conditions of the service braking or the and the operational condition for~~ another braking different from the service braking, and

22

a travel modulating device which modulates the travel of the operational member in the service braking maneuver to become substantially same even in different braking conditions by the service braking and the another braking by using the discharge pressure of the pump controlled by said braking force control device.

2. (original) A brake apparatus as claimed in claim 1, wherein said travel modulating device controls the travel of said master cylinder piston by using the discharge pressure of the pump controlled by said braking force control device.

3. (currently amended) A brake apparatus as claimed in claim 1 ~~or 2~~, wherein said pump discharges the discharge pressure by using hydraulic fluid of said master cylinder pressure chamber and the

discharge pressure of the pump controlled by said braking force control device is discharged to wheel cylinders as wheel cylinder pressure.

b1
and
4. (currently amended) A brake apparatus as claimed in ~~any one of claims 1 through 3~~ claim 1, wherein said travel modulating device is provided in said master cylinder coaxially with said master cylinder piston.

Q21
5. (currently amended) A braking apparatus as claimed in ~~any one of claims 2 through 4~~ claim 3, wherein said master cylinder piston comprises a first piston which travels when receives the input, and a second piston which is fluid-tightly and slidably disposed relative to said first piston, wherein said second piston is moved relative to said first piston by applying said wheel cylinder pressure to said second piston, thereby controlling the travel of said first piston.

6. (currently amended) A brake apparatus as claimed in claim 5, wherein said second piston is formed in a cylindrical shape having an outer peripheral step, and is fluid-tightly and slidably fitted in an axial bore of a housing of the master cylinder or in a bore of a cylindrical member fixed to said housing, and said first piston is fluid-tightly and slidably fitted in said second piston, said brake apparatus further comprising a control pressure chamber into which said wheel cylinder pressure is introduced and which is formed between the an outer periphery of said second piston and the an inner periphery of the axial bore of said housing or the an inner periphery of a bore of said cylindrical member and is defined by the outer peripheral step of said second piston, wherein said wheel cylinder pressure introduced into said control pressure chamber acts on said outer peripheral step of said second piston, thereby controlling the travel of said first piston.

b1
cont

7.(currently amended) A brake apparatus as claimed in claim 5, wherein said second piston is formed in a cylindrical shape having an inner peripheral step, and said first piston is fluid-tightly and slidably fitted in an axial bore of said second piston, said brake apparatus further comprising a control pressure chamber into which said wheel cylinder pressure is introduced and which is formed between ~~the~~ an inner periphery of said second piston and ~~the~~ an outer periphery of said first piston and is defined by the inner peripheral step of said second piston, wherein said wheel cylinder pressure introduced into said control pressure chamber acts on said inner peripheral step of said second piston, thereby controlling the travel of said first piston.

Q1
Q2

8.(currently amended) A brake apparatus as claimed in claim 4, wherein said input shaft, which is moved by the input according to the travel of the operational member, is movable relative to said master cylinder piston, said brake apparatus further comprising a control spring which is disposed in a compressed state between said input shaft and said master cylinder piston for controlling the travel of said input shaft, wherein said input of said input shaft and the spring force of said control spring act in ~~the~~ a same direction, said wheel cylinder pressure acts on said input shaft against said input and the spring force of said control spring, and said wheel cylinder pressure is controlled such that ~~the force~~ forces produced by said wheel cylinder pressure, said input, and the spring force of said control spring are balanced.

9.(currently amended) A brake apparatus as claimed in ~~any one of claims 1 through 3~~ claim 1, wherein said travel modulating device is located out of ~~the~~ a central axis of said master cylinder piston.

10.(currently amended) A brake apparatus as claimed in claim 9, wherein said ~~operational~~ travel modulating device has a travel

b1
cont

modulating piston for controlling the travel of said master cylinder piston, said travel modulating piston is moved by applying said master cylinder pressure to said travel modulating piston in one direction and applying ~~said~~ a wheel cylinder pressure to said travel modulating piston in a direction opposite to said one direction, thereby controlling the travel of said master cylinder piston.

Q2/cont

11.(original) A brake apparatus as claimed in claim 10, wherein said travel modulating piston is composed of a large-diameter piston portion at its one side portion and a small-diameter piston portion at it's the other side portion, said master cylinder pressure acts on said large-diameter piston portion and said wheel cylinder pressure acts on said small-diameter piston portion.

12.(original) A brake apparatus as claimed in claim 10, wherein said travel modulating piston is composed of a large-diameter piston portion at its one side portion and a small-diameter piston portion at it's the other side portion, said master cylinder pressure acts on said large-diameter piston portion and said wheel cylinder pressure acts on a step between said large-diameter piston portion and said small-diameter piston portion.

13.(currently amended) A brake apparatus as claimed in ~~any one of claims 10 through 12~~ claim 10, further comprising a biasing means for biasing said travel modulating piston in a direction opposite to ~~the~~ an action of said master cylinder pressure, wherein said wheel cylinder pressure is controlled such that ~~the~~ a force produced by said master cylinder pressure, ~~the~~ a force produced by said wheel cylinder pressure, and ~~the~~ a biasing force of said biasing means are balanced.

14.(currently amended) A brake apparatus as claimed in ~~any one of claims 11 through 13~~ claim 11, wherein said large-diameter piston

portion is sealed by a metal seal and said small-diameter piston portion is sealed by at least either a metal seal or an elastic seal.

b1
cont
15. (currently amended) A brake apparatus as claimed in ~~any one of claims 1 through 14~~ claim 1, wherein in ~~the~~ an event of failure of said pump, said master cylinder pressure is supplied to ~~said~~ wheel cylinders.

21
16. (currently amended) A brake apparatus as claimed in ~~any one of claims 1 through 15~~ claim 1, wherein the input is applied to said master cylinder piston after intensified by a brake pressure intensifying device at a preset servo ratio by using pressure of a pressure source, and said servo ratio is set smaller than the servo ratio normally used for the service braking.

17. (currently amended) A brake apparatus as claimed in claim 16, wherein in ~~the~~ an event of failure of said pressure source, ~~the~~ a force applied to said operational member is transmitted through said brake pressure intensifying device without magnification.

18. (original) A brake apparatus as claimed in claim 1, wherein said travel modulating device controls the travel of said input shaft according to the discharge pressure of the pump controlled by said braking force control device.

19. (currently amended) A brake apparatus as claimed in claim 18, wherein said travel modulating device has a travel control spring disposed between said master cylinder piston and said input shaft, and said travel modulating device shortens the travel of said input shaft such that the discharge pressure of the pump controlled by a pressure control valve, ~~the~~ a spring force of said travel control spring, and said input are balanced.

b1
cont

20.(currently amended) A brake apparatus as claimed in claim 18 ~~or~~
19, wherein said braking force control device controls ~~such that~~
the discharge pressure of said pump is to become greater when said
another braking different from said service braking is not
conducted, and ~~the discharge pressure of said pump is to become~~
smaller when said another braking is conducted.

21.(currently amended) A brake apparatus as claimed in ~~any one of~~
~~claims 18 through 20~~ claim 18, wherein said master cylinder piston
is operated with the discharge pressure of said pump controlled by
said braking force control device, and wheel brakes are actuated
with master cylinder pressure developed by this operation of said
master cylinder piston.

22.(currently amended) A brake apparatus as claimed in ~~any one of~~
~~claims 18 through 20~~ claim 18, wherein wheel brakes are actuated
with the discharge pressure of the pump controlled by said braking
force control device.

23.(currently amended) A brake apparatus as claimed in ~~any one of~~
~~claims 1 through 22~~ claim 1, wherein said another braking is a
regenerative braking.